### § 179.1

179.500-16 Tests of pressure relief devices. 179.500-17 Marking.

179.500-18 Inspection and reports.

APPENDIX A TO PART 179—PROCEDURES FOR TANK-HEAD PUNCTURE-RESISTANCE TEST APPENDIX B TO PART 179—PROCEDURES FOR SIMULATED POOL AND TORCH-FIRE TEST-

AUTHORITY: 49 U.S.C. 5101-5128; 49 CFR 1.81 and 1.97

Source: 29 FR 18995, Dec. 29, 1964, unless otherwise noted. Redesignated at 32 FR 5606, Apr. 5, 1967.

## Subpart A—Introduction, Approvals and Reports

#### §179.1 General.

- (a) This part prescribes the specifications for tanks that are to be mounted on or form part of a tank car and which are to be marked with a DOT specification.
- (b) Except as provided in paragraph (c) of this section, tanks to which this part is applicable, must be built to the specifications prescribed in this part.
- (c) Tanks built to specifications predating those in this part may continue in use as provided in §180.507 of this subchapter.
- (d) Any person who performs a function prescribed in this part, shall perform that function in accordance with this part.
- (e) When this part requires a tank to be marked with a DOT specification (for example, DOT-105A100W), compliance with that requirement is the responsibility of the tank builder. Marking the tank with the DOT specification shall be understood to certify compliance by the builder that the functions performed by the builder, as prescribed in this part, have been performed in compliance with this part.
- (f) The tank builder should inform each person to whom that tank is transferred of any specification requirements which have not been met at time of transfer.

[Amdt. 179–17, 41 FR 38183, Sept. 9, 1976, as amended by Amdt. 179–50, 60 FR 49076, Sept. 21, 1995; 68 FR 48571, Aug. 14, 2003]

## § 179.2 Definitions and abbreviations.

- (a) The following apply in part 179:
- (1) AAR means Association of American Railroads.

- (2) Approved means approval by the AAR Tank Car Committee.
- (3) ASTM means American Society for Testing and Materials.
  - (4) [Reserved]
- (5) Definitions in part 173 of this chapter also apply.
  - (6) F means degrees Fahrenheit.
- (7) NGT means National Gas Taper Threads.
- (8) NPT means an American Standard Taper Pipe Thread conforming to the requirements of NBS Handbook H-28 (IBR, see §171.7 of this subchapter).
  - (9) [Reserved]
- (10) Tank car facility means an entity that manufactures, repairs, inspects, tests, qualifies, or maintains a tank car to ensure that the tank car conforms to this part and subpart F of part 180 of this subchapter, that alters the certificate of construction of the tank car, that ensures the continuing qualification of a tank car by performing a function prescribed in parts 179 or 180 of this subchapter, or that makes any representation indicating compliance with one or more of the requirements of parts 179 or 180 of this subchapter.
  - (11) Tanks means tank car tanks.
  - (b) [Reserved]

[29 FR 18995, Dec. 20, 1964. Redesignated at 32 FR 5606, Apr. 5, 1967, and amended by Amdt. 179–10, 36 FR 21344, Nov. 6, 1971; Amdt. 179–50, 60 FR 49076, Sept. 21, 1995; Amdt. 179–50, 61 FR 33255, June 26, 1996; 63 FR 52850, Oct. 1, 1998; 66 FR 45186, 45390, Aug. 28, 2001; 68 fR 75759, Dec. 31, 2003]

# §179.3 Procedure for securing approval.

- (a) Application for approval of designs, materials and construction, conversion or alteration of tank car tanks under these specifications, complete with detailed prints, must be submitted in prescribed form to the Executive Director—Tank Car Safety, AAR, for consideration by its Tank Car Committee and other appropriate committees. Approval or rejections of applications based on appropriate committee action will be issued by the executive director.
- (b) When, in the opinion of the Committee, such tanks or equipment are in compliance with the requirements of this subchapter, the application will be approved.